

LVLL/ULEC LANDSCAPE LIGHTING LOW VOLTAGE CABLE



Rated 150 Volts
Rated -20°C to +60°C

Approved for Outdoor
Use (Sunlight Resistant)
Suitable for Direct Burial

Stranded Copper
Conductors

Black PVC
Insulation/Jacket

APPLICATIONS Suitable for use as follows:

- Outdoor Accent Lighting
- Landscape Lighting
- Security Lighting
- Exposure to Direct Sunlight (Sunlight Resistant)
- Direct Burial

STANDARDS & REFERENCES

- UL (Miscellaneous Wire – Low Energy Circuit Cable)
- C-UL

CONSTRUCTION

- Conductors:
Two fully annealed bare stranded copper conductors
- Insulation/Jacket:
Premium-grade PVC
-20°C to +60°C
- Final Assembly:
Insulated/Jacketed conductors duplexed in a flat construction for easy tear-down during installation
- Color:
Black is standard
Available in white or brown, but subject to minimum order quantity

WEIGHTS, MEASUREMENTS AND PACKAGING

CONDUCTOR SIZE (AWG)	CONDUCTOR STRANDING (#/AWG)	NOMINAL OVERALL DIAMETER (mils)	NOMINAL JACKET THICKNESS (mils)	WEIGHT (lbs/1000 ft)	PUT-UP (ft)
16/2	26/30	156 X 307	48	41	250
14/2	41/30	166 X 341	46	55	250
12/2	65/30	186 X 370	47	69	250
10/2	104/30	205 X 405	47	107	250
8/2	7 X 24/30	270 X 530	62	163	250