

Project: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Location: \_\_\_\_\_

Contact/Phone: \_\_\_\_\_

## US-LM3575W

3" LED Square Smooth Retrofit Kit



### DESCRIPTION

The US-LM3575W is a 3" LED Square Smooth Retrofit kit. It is compatible with most 4" recessed standard housings. Ideal for both remodel or new construction applications. The retrofit kit comes with a disconnect screw-in base lease for easy installation into standard incandescent sockets.

### PRODUCT SPECIFICATIONS

- White painted Diecast body is appropriate for heat dissipation.
- Oversized trim ring constructed from one-piece diecast.
- 3 Tension clips pre-installed on unit for easy installation.
- E26 medium screw-base Edison connector provides easy retrofit of incandescent housings.  
(GU10 and GU24 socket adaptor available - sold separately)

### LED LIGHT ENGINE

- Protected LED driver performs at 120V (120-277V available).
- Dimming down to 5% with most dimmers (at 120V only).
- CCT 2700K, 3000K, 4000K, 5000K available
- CRI ≥ 80 or ≥ 90
- Long life LED chips guaranteed up to 36,000 hours.

### WARRANTY

Guaranteed three years from the purchase date of the product, against mechanical defects in manufacturing.

### LISTINGS

- cUL us classified
- Energy star qualified
- Title 24 compliant
- Wet locations (Not suitable for coastal/salt water area)
- Damp locations
- RoHS compliances
- Tested in accordance with IESNA LM79 & LM80

### PERFORMANCE DATA

	3K
Input Voltage	120V
Input Power	9W
Frequency	50 / 60Hz
Operation temp	-30C ~ 40C (-22F ~ 104F)
Lumens	640
CRI	≥ 90

### SPECIFICATIONS / DIMENSIONS

