



LED T5 Direct Fit Replacement Lamps









128 lpw

50,000 hours

features

- Directly replaces 54W T5HO fluorescent lamps
- T5HO fluorescent ballast compatible
- No socket changes; for use with non-shunted socketed fixtures
- Operates on most popular electronic programmed start fluorescent T5HO ballasts
- No rewiring or modifications of any kind required
- Instantaneous full light output upon power-up
- Choice of 4000K or 5000K CCT
- Frosted glass lens reduces visual glare
- Environment-friendly, no mercury or lead
- 5 year product warranty
- Suitable for fully enclosed fixtures







performance

- 3,200 lumens @ 25W (bare lamp)
- 80+ CRI
- Beam Angle: 185°
- THD: <20%
- Power Factor: 0.98
- Rated Lifetime: 50,000 hours @ L70
- Suitable for damp locations
- Suitable for use in fixtures where ambient temperature is between -4°F (-20°C) and 113°F (45°C)

- Does not operate on emergency battery
- Does not operate on magnetic ballasts
- Does not operate on T8 or T12 ballasts

applications

- Highbays
- Troffers
- Industrial Strips
- Cove Lighting
- Vapor Tights
- Warehouses
- Stairwells
- Cold Storage















LED T5 Direct Fit Replacement Lamps

ordering information

| Order Code | Item # | Length | Lumens | Bare Lamp Watts | System Watts | Volts (Ballast Dependent) | ССТ | CRI | Glass Tube | Beam Angle | Life Hours |
|---------------|-----------------------|--------|--------|-----------------------|-----------------|------------------------------|-------|-----|---------------|---------------|---------------|
| 09178 | LED32T5HO/46/840-G6DR | 46" | 3,200 | 25 | 28 | 120-277V, 347V | 4000K | 80+ | Frosted | 185° | 50,000 |
| 09179 | LED32T5HO/46/850-G6DR | 46" | 3,200 | 25 | 28 | 120-277V, 347V | 5000K | 80+ | Frosted | 185° | 50,000 |
| 185° THOUGH | | | | | | | | | | | |







