


**NOTES:**

1. Output voltage in table 1 with 120VAC applied and fully loaded.
2. Maximum no load input current : 0.05A
3. Enclosure Temperature does not exceed 55°C in a 40°C ambient, fully loaded.
4. The actual transformer 5VA is encapsulated in the enclosure.
5. The transformer is dimmable with all dimmers that provide symmetrical form of the current under any condition.
6. Input and output terminal block UL rated 300V 20 Amps. 20-12 AWG
7. The transformer uses a class B (130°C) insulation system.
8. Wiring compartment has 2 side knockouts sized for 3/4 inch screw cable connectors.
9. The removable wiring compartment is secured in place by clips and one screw.
10. The enclosure powder coated black.
11. The label contains Technomagnet's catalog number and electrical rating.
12. The Transformer has thermal self-reset 0.8A circuit breaker on secondary and primary side.
13. The transformer is cETLus listed, control # 4005509 confirms to UL STD 1310, certified to CSA STD C22.2 #223.



**Table 1.**

Output Volts	
120AC	
24VDC	

		Interactive Lighting Servers		15547 Cabrito Road Unit A Van Nuys, CA 91406	
				Page 1 Of 1	Scale: no scale Tolerance: ±
DRW.	Name	Date	Title:	Compact indoor 24VDC 5VA Low voltage Transformer.	
CHK.	APR.	Rev. A	Part # MF5S24DC		